

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction products

Road restraint systems – Part 5: Product requirements and evaluation of conformity for vehicle restraint systems

Safety barriers for use in vehicle restraint system in circulation areas, with specification and performance as specified on page 2-3 in this certificate.

Product name: SafeLine-M

placed on the market under the name or trademark of

Saferoad Vik Örsta AS

Postboks 193
NO-6150 Ørsta, Norway

and produced in the manufacturing plants

VV, 30004, 30077, 30092, 31222, 31548, 32816 and 32964

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in annex ZA of the standards

EN 1317-5:2007+A2:2012 and EN 1317-5:2007+A2:2012/AC:2012

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 2019-06-03 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Issued by notified body 0402.

The validity of this certificate can be verified at RISE homepage.



Martin Tillander
Director Product Certification

Certificate 0402-CPR-SC0213-19 | issue 5 | 2026-06-06

RISE Research Institutes of Sweden AB | Certification

Box 857, SE-50115 Borås, Sweden

+46 10 516 50 00 | certifiering@ri.se | www.ri.se

1346183

This document is the property of RISE and may not be reproduced other than in full, except with the prior written approval by RISE

Specification

SafeLine-M cc 3.0 / 6.0

Post distance	3.0 or 6.0 m
Height above road surface:	Total: 0.6 m, Rail 0.55 m (centre of rail) 1.1 m with Pedestrian add-on
Post:	C-profile: 120 × 40 × 25 mm Thickness: 5 mm Total length for posts: -for soil: min. 1300 mm -for socket: min. 1070 mm -for base plate: 515 mm, incl. base plate 540 mm -for plinth: 415 mm, incl. base plate 440 mm (plinth height 100 mm) -for anchor plate: 540 or 573 mm Steel S355 driven into ground for minimum 0.7 m
Rail:	Oval open profile: 200 × 98 mm Thickness: 3 mm Steel S420 Rail beam joint either 1500 mm or 3000 mm from closest post Length: 5995 mm, for removable section 5893 mm
Socket:	Closed profile: 131 × 51 mm Thickness: 2.5 - 4 mm Length: 500 mm Steel S355
Baseplate:	Plate: 200 × 200 × 25 mm Steel S355 Steel tape: 44 × 3 mm Steel S235 Anchoring bolts: min. 4xM20, 140 × 140 placement
Anchor plate glued to asphalt:	1000 × 850 × 20 mm Steel S355

Pedestrian add-on for cc 3.0 m:

Handrail: pipe Diameter 88.9 mm
Thickness: 2.9 mm
Material: Steel S355J2
Post: pipe
Diameter: 40 mm
Thickness: 2.9 mm
Material: Steel S355J2

Removable section for cc 3.0 m:

Joint with overlapping plates
Locking pin to post:
Steel rod Ø19 mm
Material: S355
Locking pin between rail sections
Double steel rod Ø30 mm
Material: S355

Performance

Classification according to EN 1317-5:2007+A2:2012/AC:2012 (EN 1317-2:2010)

Product	Containment level	Impact severity level	Normalized working width, class [m]	Normalized dynamic deflection, [m]	Normalized vehicle intrusion class, [m]
SafeLine-M H1-W3-CC3 CC 3 m	H1	A	W3 (1.0)	0.9	VI6 (2.1)
SafeLine-M H1-W3-CC3 with baseplate on plinth CC 3 m	H1	A	W3 (0.8)	0.7	VI6 (1.8)
SafeLine-M N2-W4-CC3 CC 3 m	N2	A	W4 (1.3)	1.2	N/A
SafeLine-M N2-W4-CC3 with baseplate on plinth CC 3 m	N2	A	W4 (1.1)	1.0	N/A
SafeLine-M N2-W4-CC6 CC 6 m	N2	A	W4 (1.3)	1.2	N/A
SafeLine-M N2-W4-CC6 with baseplate on plinth CC 6 m	N2	A	W4 (1.1)	1.1	N/A
SafeLine-M L1-W4-CC3 CC 3 m	L1	A	W4 (1.3)	1.2	VI6 (2.1)
SafeLine-M L1-W4-CC3 with baseplate on plinth CC 3 m	L1	A	W4 (1.1)	1.0	VI6 (1.8)
SafeLine-M cc 3.0 m Removable Barrier Section in Socket Foundation	H1	A	W3 (1.0)	0.9	VI6 (2.1)
SafeLine-M cc 3.0 m with Pedestrian add-on	H1	A	W3 (1.0)	0.9	VI6 (1.7)

Classification according to EN 1317-5:2007+A2:2012/AC:2012 (EN 1317-2:2010)

Product	Durability	Resistance to snow removal class
SafeLine-M	Hot dip galvanized, acc. To EN ISO 1461	Class 4