

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction products

## Road restraint systems – Part 5: Product requirements and evaluation of conformity for vehicle restraint systems

Safety barriers for use in vehicle restraint systems in circulation areas, with specification and performance as specified on page 2-4 in this certificate.

### Product name: Ørsta Brurekkverk (Orsta Bridge Parapet)

placed on the market under the name or trademark of

#### VIK Ørsta AS

Postboks 193  
NO-6150 Ørsta, Norway

and produced in the manufacturing plants

VØ, 31222, 30092 and 32062

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in annex ZA of the standards

### EN 1317-5:2007+A2:2012 and EN 1317-5:2007+A2:2012/AC:2012

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

### constancy of performance of the construction product.

This certificate was first issued on 2011-04-04 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Issued by notified body 0402.

The validity of this certificate can be verified at RISE homepage.



Martin Tillander  
Director Product Certification

Certificate 0402-CPR- SC0240-11 | issue 6 | 2024-11-25

RISE Research Institutes of Sweden AB | Certification

Box 857, SE-50115 Borås, Sweden

+46 10 516 50 00 | certifiering@ri.se | www.ri.se

292464

This document is the property of RISE and may not be reproduced other than in full, except with the prior written approval by RISE

## Specification

Ørsta Brurekkverk

Height above road surface	Total: 1.2 – 1.4 m Upper rail: 1.15 – 1.35 m (centre of rail)
Post distance	2.0 m
Steel post dimension	Tube $\text{Ø}139.7 \times 4.0$ mm Length, with total height 1.2 m: Base plate on plinth: 0.905 m Base plate on road surface: 1.085 m Length, with total height 1.4 m: Base plate on plinth: 1.140 m
Base plate	Steel S355 200 × 200 × 20 mm 250 × 250 × 25 mm
Concrete edge beam	Steel S355 Height: 150 mm Distance between centre of post and edge 220 – 320 mm
Steel rail	Hand-, mid- and lower rail: $\text{Ø}114.3 \times 3.6$ mm Steel S355
Handrail	Joint position vertically aligned with mid- and lower rail
Infill pipes	Tube $\text{Ø}60 \times 3.65$ mm Steel S355
Birsta Noise Barrier and attachment brackets	Birsta Noise Barrier with specifications in AVCP 3 report with designation SC0361-17. Upper bracket 220 × 205 × 137 mm, thickness 12 mm Lower bracket 200 × 155 × 92 mm, thickness 8 mm
Optional feature infillings mounted between the steel posts	Horizontal pipe Vertical bars Net fence

## Performance

Classification according to EN 1317-5:2007+A2:2012/AC:2012 (EN 1317-2:2010)

Product	Containment level	Impact severity level	Normalized working width, class [m]	Normalized dynamic deflection, [m]	Normalized Vehicle intrusion, class [m]
Ørsta Brurekkverk cc 2.0 m	H2	B	W2 (0.8)	0.5	VI4 (1.1)
Ørsta Brurekkverk with Birsta Noise Barrier cc 2.0 m	H2	B	W2 (0.8)	0.5	VI4 (1.1)
Ørsta Brurekkverk H=1200 without plinth cc 2.0 m	H2	B	W2 (0.8)	0.5	VI4 (1.0)
Ørsta Brurekkverk H=1400 with plinth (150) cc 2.0 m	H2	B	W2 (0.8)	0.4	VI4 (0.8)
Ørsta Brurekkverk Lower infill pipe on 1200 mm high post without plinth cc 2.0 m	H2	B	W2 (0.8)	0.5	VI4 (1.1)
Ørsta Brurekkverk Longitudinal joint profile and aligned vertical position cc 2.0 m	H2	B	W2 (0.8)	0.5	VI4 (1.1)
Ørsta Brurekkverk Changed shape of HDG holes in top plate cc 2.0 m	H2	B	W2 (0.8)	0.5	VI4 (1.1)
Ørsta Brurekkverk cc 2.0 m	L2	B	W2 (0.8)	0.5	VI4 (1.1)
Ørsta Brurekkverk with Birsta Noise Barrier cc 2.0 m	L2	B	W2 (0.8)	0.5	VI4 (1.1)
Ørsta Brurekkverk H=1200 without plinth cc 2.0 m	L2	B	W2 (0.8)	0.5	VI4 (1.0)
Ørsta Brurekkverk H=1400 with plinth (150) cc 2.0 m	L2	B	W2 (0.8)	0.4	VI4 (0.8)
Ørsta Brurekkverk Lower infill pipe on 1200 mm high post without plinth cc 2.0 m	L2	B	W2 (0.8)	0.4	VI4 (0.8)
Ørsta Brurekkverk Longitudinal joint profile and aligned vertical position cc 2.0 m	L2	B	W2 (0.8)	0.5	VI4 (1.1)
Ørsta Brurekkverk Changed shape of HDG holes in top plate cc 2.0 m	L2	B	W2 (0.8)	0.5	VI4 (1.1)
Ørsta Brurekkverk cc 2.0 m	N2	B	W1 (0.5)	0.3	N/A

Classification according to EN 1317-5:2007+A2:2012/AC:2012 (EN 1317-2:2010)

Product	Durability	Resistance to snow removal class
Ørsta Brurekkverk	Hot dip galvanized, acc. To EN ISO 1461	Class 4